

FlowMeters

Paddle Wheel Flowmeters For Clear Water

- Paddle type turbine flowmeters for various Liquids.
- Sizes - 12mm to 1200 mm
- Max. operating temp - 70⁰ C
(For higher temp.sp. material available)
- Max. operating pressure - 10 Kg/cm²
- Power Supply - 230V AC / 12V DC / 24V DC
- Accuracy - ± 2% on full scale valve.
- Mounting - Panel / Wall / Field Mounted Versions
- Display - LED / LCD in one line / Two line
- Reading in LPS / LPM / M³ / hr
- Measure Flow instantly
(Velocity must be more than 0.5 m/sec.)
- Material - pp/ms/ss pipe and turbine is in pp/ss (PTFE on request)
- Programmable Relay outputs
- 4-20 ma output
- Microprocessor based signal processing
- Also available with totallizer
- Routine test of pump become very easy.
- Measurement tank or "V" notch is not required.
- Very reasonable price & fast delivery



Also Available

- Aluminum motor body
- Stainless steel spares
- stainless steel pumps

EASY CALIBRATION

<u>PIPE SIZE</u>	<u>NORMAL RANGE</u>
12	7-70 LPM
20	10-100 LPM
25	15-150 LPM
40	32-320 LPM
50	58-580 LPM
65	90-900 LPM
76	135-1350 LPM
100	250-2500 LPM
150	570-5700 LPM

